



Technical Bulletin

Which Coating Should You Use? What is the Difference?

	Solvent Based Polyurethane	Oil Based Coating	Water Based Coating
Substrate to be Coated	Timber, Parquetry, Cork & Concrete	Timber & Parquetry	Timber, Parquetry & Cork
Appearance on Timber	Deep protective wear layer	Enhances grain appearance	Protective wear layer
Colour on Timber	Rich & Dark	Deep & Dark Colour	Natural Colour
Gloss Level Available	Gloss, Semi-Gloss, Satin & Matt	Gloss & Satin	Gloss, Satin & Matt
Durability	Excellent	Moderate	Very Good
Time Between Coat	8 Hours (shorter with DURAPOL Accelerator Additive)	24 Hours	2-4 Hours
Disruption to Occupants	High	Moderate	Minimal
Recoat Time Frame	4-8 Years	2-3 Years	5-6 Years
Maintenance	Regular Cleaning	Regular Cleaning/ Recoat When Needed	Regular Cleaning & Maintenance
Suitable Applications	Commercial Domestic	Domestic & Sports Floors	Commercial, Domestic & Sports Floors

PLEASE CONTACT POLYCURE'S TECHNICAL SERVICE DEPARTMENT OR YOUR LOCAL POLYCURE ACCOUNT EXECUTIVE FOR FURTHER FREE ADVICE.

www.polycure.com.au

